

Product Name: Separate Fixed Ultrasonic Flowmeter
Product Model: TUF-2000SB



+



+



One pair of TM-1 SENSOR

- Dual-magnet structure, easy installation
- protection grade IP65
- Temperature: 0 ~ 90℃,
- pipe size: DN50~1000mm

Special Cable

Product Introduction :
Main Features:

Features	Description
High Accuracy measuring	Linearity: better than 0.5%, Repeatability: better than 0.2%, Accuracy: better than ±1%
Wide measuring range	Measuring pipe size from DN50 to DN1000. Note: You may select other types sensor for measuring other pipe sizes .
Chinese & English menu	Different version UFM can support Chinese or English display, easy to operate.
High Reliability	Adopt low voltage, multi-pulse technology to improve accuracy, useful life and reliability.
Strong Anti-interference	Dual-balance signal differential receiver/driver circuit to avoid interference of converter, TV tower, high voltage line etc.
Others	Volume: 170×180×56mm All-filling rubber process, protection grade IP65 Optional all types of sensors Input and output signals: 4 ~20mA analog input: 3 line, OCT output: 2 line, 4 ~ 20mA output: 1 line, thermal measurement functions and so on. Support METER-BUS protocol, MODBUS protocol, Fuji expanded agreement, simple water meter agreement, other manufacturers protocol.

Installation

